

**NUX**  
Vintage Series

Owner's Manual

**ATLANTIC**  
— delay & reverb —

**NDR-5**

#### Copyright

Copyright 2017 Cloud Technology Co. All rights reserved. MXR and **Musicamp II** are trademarks of Cloud Technology Co. MXR Model Number is used in the printed and electronic parts of this equipment. MXR and MXR are trademarks or affiliated with Cloud Technology Co. Japan.

MXR and every effort has been made to ensure the accuracy and content of this manual. Cloud Technology Co. reserves representation or warranty regarding the contents.

### WARNINGS-IMPORTANT SAFETY INSTRUCTIONS BEFORE CONNECTING, READ INSTRUCTIONS

**WARNING:** To reduce the risk of fire or electric shock, do not expose this appliance to rain or moisture.

**CAUTION:** To reduce the risk of fire or electric shock, do not remove covers. No user-serviceable parts inside. Refer servicing to qualified service personnel.

**CAUTION:** This equipment has been tested and found to comply with the limits for a Class B digital device pursuant to Part 15 of FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) if the device does cause any interference received, the user must take all necessary steps to correct the interference.



The lightning symbol within a triangle means "high voltage caution." It indicates the presence of information about high voltage that is present in this or adjacent circuit.



The exclamation point within a triangle means "caution." Please read the information that is on another page.

1. Use only the supplied power supply or power cord. If you do not have the type of power available, consult your dealer or local power company.
2. Do not place near heat sources, such as radiators, heat registers, or appliances which produce heat.
3. Guard against objects or liquids entering the equipment.
4. Do not attempt to service this product yourself, as opening or removing covers may expose you to dangerous voltage points or other risks. Refer all servicing to qualified service personnel.
5. Refer all servicing to qualified service personnel. Servicing is required when the equipment has been damaged in any way, such as when the power supply cord or plug is damaged, liquid has been spilled or objects have fallen into the equipment, the equipment has been exposed to rain or moisture, does not operate normally or has been dropped.
6. The power supply cord should be unplugged when the unit is to be stored for long periods of time.
7. Protect the power cord from being stepped on or pinched particularly at plugs, connections, switches and in the strain relief area.
8. Prolonged exposure to high volume levels may cause irreversible hearing loss and/or damage. Always be sure to practice "safe listening".

*Follow all instructions and heed all warnings  
**KEEP THESE INSTRUCTIONS!***

One of the best Delay and Reverb algorithms in this metal box. MXR Atlantic Delay & Reverb pedal have special-select 3 Delay & 3 Reverb effects with an additional dreamy Shimmering effect. And now with the MXR's latest Core Image technology, Verdugo series new effect pedals are offering one of the best sound enhancements. We are choosing the best ideas to make it real for a musician.

MXR Atlantic Delay & Reverb pedal also has inside routing control between the effects, you can choose which effect comes first. On serial mode you can create a deep reflection reverb with wet or dry repeats, or you can split your guitar signal and add both effects in parallel chain. Each effect will be mixed with separated dry signals.

It has 6.35 mm mono jack input and 2 outputs you can also connect stereo for the real Delay & Reverb experience.

It has an Input Level toggle switch, you can optimize the input signal with your signal level.

## Control panel



## Control panel



### 70's (40ms - 800ms)

Retro-delay needs modern technology, without losing the real-life BBD-effected repeats, so essential for capturing the 70's retro feel.

### 80's (55ms - 550ms)

A warm & dusty tape-echo machine effect, packed with an array of analogue-only goodies. Saturated colors that turn any sound into vintage. Tweak the Repeat knob to the max and use the Time knob to get an experience, just like the real Tape-Echo Machine.

## Control panel

### BO's (50ms - 100ms)

A digital era invention, crystal clear repeats. Digitally-copied clean repeats carries your signal without absolutely zero color particles. This is the best option if you don't want to mix your favorite chorus with another colorization effect--or your favorite modulation effect.

### Level (Delay) Knob

Controls the wet/dry balance. Adjusts the volume for your repeats.

### Repeat Knob

Varies the numbers of repeats. When set to the MAX sustained runaway will start. You can create an infinite sustained runaway on BO's Delay mode.

### Time Knob

Controls the delay time. Turning the Time knob while repeating can produce interesting pitch effects.

Time knob also changes the TAP subdivision on TAP TEMPO mode. (See TAP TEMPO)

### Delay LED Indicator

It also shows the TAP TEMPO.

### Delay Footswitch

Engages and disengages the Delay effect. And activates TAP TEMPO.

## Control panel



**TAP TEMPO:** Instantly synch-up your delays with the tempo you want to accompany. Simply tap the tempo with your foot. TAP TEMPO Speed range is 125 ms - 1500 ms for all delay types.

**Delay Pattern:** Before you set the TAP TEMPO, use the Time Knob and choose any desired time signature to change the delay pattern. When TAP TEMPO is engaged, your repeats will create a delay pattern according to selected time signature.

**TAP Values:** 1/8, 1/6, 1/4, 1/3, 1/2, 3/4 and 1

### Spring Reverb

Creates a polyphonic atmosphere filter that catches the sound reflections from deep down spring reverb tank. You can adjust the tank size with the level knob and set the reflection distance with the decay knob.

### Plate Reverb & Shimmer

Straight and clean reflections inside a flat-walled room. You can control the room-size with the Level knob and then tweak the Delay bounce point with the Decay knob.

If you hold down the Reverb switch, straight reflections will be heated and swirled throughout the inside of the room creating a Shimmer effect.

### Room Reverb

The sound of a well-designed hall. Whether the hall size is big or small, the reflections will be emitted by wall furniture. You can adjust the interior hall-size, from a small garage to a huge structure with the Level knob and increase or decrease the number of objects on the walls with the Decay Knob. Less decay means more objects and faster reflection fading.

## Control panel

---

### Level (Reverb) Knob

Controls the balance of wet signal and dry signal. Adjust the Reverb level and size of the area.

### Decay Knob

Controls the decay time of the wet signal. Range can depend on selected reverb type.

### Reverb LED indicator

### Reverb Footswitch

Engages and disengages the Reverb effect. And controls the Shimmering effect.

**Shimmer:** Choose Plate Reverb. Then hold the Reverb foot-switch (as long as you want) until your effect takes flight. The effect will fade-out when you release the foot-switch.

### Input

6.35 mm Stereo Jack input.

### Input Level Switch

Adjusts the input impedance. If the input signal is too loud, switch to +4 dB for increase the headroom.

### Routing Switch

You can use the Delay and Reverb effect with parallel or serial connection. In serial mode, you can change the signal routing. Before plug-in the power cable, hold one of the effect button which you want to come first, then plug-in the power cable.

## Control panel

---

### Stereo Outputs

Use the right output for mono connection.


### Micro USB Input

To connect to PC.

### Power Input

9v 8-8-8

## Connection Methods



Atlantic's Input jack can support stereo cable as insert (send/ return) method. Please see the blow two drawings:

Using "T" cable connection




Using "Insert" cable connection



## Inside Routing

**DELAY first**



1. Set SERIAL




2. Hold down the Delay Footswitch



3. Plug-in the power cable

**REVERB first**



1. Set SERIAL




2. Hold down the Reverb Footswitch



3. Plug-in the power cable

## Inside Routing

### Parallel Routing



Set PARALLEL



## Technical specifications

- Sampling rate: 44.1KHz
- A/D Converter: 32Bit
- Signal Processing: 32Bit
- Frequency Response: 20Hz-20KHz $\pm$ 1dB
- THD+N: -100dBu (A-Weighting)
- Dynamic Range: 102dB
- Input: +16dBu
- Output: +16dBu
- Power: 9V DC (Negative tip, Optional AC9-006A adapter)
- Dimensions: 106 (L) X 115 (W) X 57 (H)mm
- Weight: 420g

### Accessories: User manual

\*Specifications and features are subject to change without notice.

#### CE mark for European Harmonized Standards

CE Mark, which is attached to our company's products of Battery mains the premise is to fully conformity with the harmonized standard(s) EN 61000-4-3:2007+A1:2011 & EN 61508-6:1:2007 Under the Council Directive 2004/70/EEC on Electromagnetic Compatibility



[www.nuxefx.com](http://www.nuxefx.com)

Made in China